

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## O2C Protection Paint

Version	Revision Date:	Print Date	Date of last issue: 11.07.2019
1.1	31.10.2019	13.01.2020	Date of first issue: 11.07.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : O2C Protection Paint

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Water-borne coatings

Recommended restrictions : within adequate application - none  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : PAGEL Spezial-Beton GmbH & Co. KG  
Wolfsbankring 9  
D-45355 Essen  
Telephone : +4920168504-0  
Telefax : +4920168504-31  
E-mail address Respon-  
sible/issuing person : labor@pagel.de, schempershofe@pagel.de

#### 1.4 Emergency telephone number

Emergency telephone num-  
ber 1 : +49613119240 GIZ Mainz

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version 1.1      Revision Date: 31.10.2019      Print Date 13.01.2020      Date of last issue: 11.07.2019  
Date of first issue: 11.07.2019

Precautionary statements : **Prevention:**  
P262 Do not get in eyes, on skin, or on clothing.  
P280 Wear protective gloves/ eye protection.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one  
2-methylisothiazol-3(2H)-one  
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Emulsion paint, aqueous

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 2; H330 Acute Tox. 3; H311 Acute Tox. 3; H301 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	$\geq 0,0025$ - $< 0,025$
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 2; H330	$\geq 0,0025$ - $< 0,025$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version 1.1      Revision Date: 31.10.2019      Print Date 13.01.2020      Date of last issue: 11.07.2019  
Date of first issue: 11.07.2019

		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	>= 0,0002 - < 0,0015
Substances with a workplace exposure limit :			
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17		>= 10 - < 20
Limestone	1317-65-3 215-279-6		>= 10 - < 20
mica	12001-26-2		>= 1 - < 10
kaolin	1332-58-7 310-194-1		>= 1 - < 10

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : First aider needs to protect himself.  
Move out of dangerous area.  
If you feel unwell, seek medical advice (show the label where possible).  
Never give anything by mouth to an unconscious person.
- If inhaled : Move to fresh air.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Do NOT use solvents or thinners.
- In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/ attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Clean mouth with water and drink afterwards plenty of water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version	Revision Date:	Print Date	Date of last issue: 11.07.2019
1.1	31.10.2019	13.01.2020	Date of first issue: 11.07.2019

Seek medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

None known.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : The product itself does not burn.  
Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.  
Material can create slippery conditions.  
Use protective shoes or boots with rough rubber sole.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Prevent further leakage or spillage if safe to do so.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version 1.1	Revision Date: 31.10.2019	Print Date 13.01.2020	Date of last issue: 11.07.2019 Date of first issue: 11.07.2019
----------------	------------------------------	--------------------------	---

### 6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8., For further information see Section 7 of the safety data sheet.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : No special technical protective measures required.  
For personal protection see section 8.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands before eating, drinking, or smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container. To maintain product quality, do not store in heat or direct sunlight. Perishable if frozen.
- Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

### 7.3 Specific end use(s)

- Specific use(s) : Please follow the technical information.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m <sup>3</sup>	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m <sup>-3</sup> 8-hour TWA of inhalable dust or 4 mg.m <sup>-3</sup> 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhalable dust approximates to			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version 1.1      Revision Date: 31.10.2019      Print Date 13.01.2020      Date of last issue: 11.07.2019  
Date of first issue: 11.07.2019

		the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
		TWA (Respirable dust)	4 mg/m3	GB EH40
Limestone	1317-65-3	TWA (inhalable dust)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable dust)	4 mg/m3	GB EH40
mica	12001-26-2	TWA (Inhalable)	10 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
		TWA (Respirable)	0,8 mg/m3	GB EH40
kaolin	1332-58-7	TWA (Respirable dust)	2 mg/m3	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/4 General methods for sampling and gravimetric analysis or respirable, thoracic and inhalable aerosols, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m-3 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version 1.1      Revision Date: 31.10.2019      Print Date 13.01.2020      Date of last issue: 11.07.2019  
Date of first issue: 11.07.2019

	dust. This means that any dust will be subject to COSHH if people are exposed to dust above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limits., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system, and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/4., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.		
	TWA (Respirable dust)	0,1 mg/m3	2004/37/EC
Further information	Carcinogens or mutagens		

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
titanium dioxide	Consumers	Ingestion	Long-term systemic effects	700,00 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	10,00 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
titanium dioxide	Sewage treatment plant	100 mg/l
	Fresh water	0,184 mg/l
	Soil	100 mg/kg dry weight (d.w.)
	Marine water	0,0184 mg/l
	Fresh water sediment	1000 mg/kg dry weight (d.w.)
	Marine sediment	100 mg/kg dry weight (d.w.)
	Intermittent use/release	0,193 mg/l

## 8.2 Exposure controls

### Personal protective equipment

Eye protection : Goggles

### Hand protection

Material : Nitrile rubber  
Glove thickness : 0,2 mm  
Protective index : Class 3

Remarks : Wear suitable gloves tested to EN374. Before removing gloves clean them with soap and water.

Skin and body protection : Long sleeved clothing  
Safety shoes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version 1.1	Revision Date: 31.10.2019	Print Date 13.01.2020	Date of last issue: 11.07.2019 Date of first issue: 11.07.2019
----------------	------------------------------	--------------------------	---

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.  
During spray application: impervious clothing

Respiratory protection : No personal respiratory protective equipment normally required.

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: No data available
Odour	: No data available
Odour Threshold	: Not relevant
pH	: not determined
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Flash point	: No data available
Evaporation rate	: Not applicable
Upper explosion limit / Upper flammability limit	: not determined
Lower explosion limit / Lower flammability limit	: not determined
Vapour pressure	: not determined
Relative vapour density	: not determined
Relative density	: not determined
Density	: 1,4400 g/cm <sup>3</sup>
Solubility(ies) Water solubility	: completely miscible
Partition coefficient: n-	: not determined



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version	Revision Date:	Print Date	Date of last issue: 11.07.2019
1.1	31.10.2019	13.01.2020	Date of first issue: 11.07.2019

octanol/water

Auto-ignition temperature : not determined

Decomposition temperature : Not applicable

Viscosity

Viscosity, dynamic : No data available

Explosive properties : Not applicable

Oxidizing properties : Not applicable

### 9.2 Other information

Flammability (liquids) : The product is not flammable.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

### 10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.  
Incompatible with acids and bases.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version 1.1	Revision Date: 31.10.2019	Print Date 13.01.2020	Date of last issue: 11.07.2019 Date of first issue: 11.07.2019
----------------	------------------------------	--------------------------	---

are not met.

### Components:

#### **2-methylisothiazol-3(2H)-one:**

Acute oral toxicity : LD50 (Rat): 120 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 0,145 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

#### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity : LD50 (Rat): 532 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

#### **reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Acute oral toxicity : LD50 (Rat): 66 mg/kg  
Method: OECD Test Guideline 401  
Acute inhalation toxicity : LC50 (Rat): 0,17 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Acute dermal toxicity : LD50 (Rat): > 141 mg/kg  
Method: OECD Test Guideline 402

### **Skin corrosion/irritation**

#### Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

### Components:

#### **Limestone:**

Remarks : According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

### **Serious eye damage/eye irritation**

#### Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version 1.1	Revision Date: 31.10.2019	Print Date 13.01.2020	Date of last issue: 11.07.2019 Date of first issue: 11.07.2019
----------------	------------------------------	--------------------------	---

### Components:

#### **Limestone:**

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

### **Respiratory or skin sensitisation**

#### Product:

Remarks : Causes sensitisation.

### Components:

#### **Limestone:**

Remarks : No data available

### **Further information**

#### Components:

#### **Limestone:**

Remarks : No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

#### Components:

#### **2-methylisothiazol-3(2H)-one:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

#### **1,2-benzisothiazol-3(2H)-one:**

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version	Revision Date:	Print Date	Date of last issue: 11.07.2019
1.1	31.10.2019	13.01.2020	Date of first issue: 11.07.2019

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

#### Components:

**reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):**

Partition coefficient: n-octanol/water : log Pow: <= 0,71  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local, regional, national and international authorities.

Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product  
080112, waste paint and varnish other than those mentioned in 08 01 11\*

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version	Revision Date:	Print Date	Date of last issue: 11.07.2019
1.1	31.10.2019	13.01.2020	Date of first issue: 11.07.2019

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.

REACH - List of substances subject to authorisation (Annex XIV) : None

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

formaldehyde (Number on list 72, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

Volatile organic compounds : Directive 2004/42/EC  
< 3 %  
< 40 g/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version	Revision Date:	Print Date	Date of last issue: 11.07.2019
1.1	31.10.2019	13.01.2020	Date of first issue: 11.07.2019

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

## SECTION 16: Other information

### Full text of H-Statements

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2004/37/EC / TWA	: Long term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Other information:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## O2C Protection Paint

Version	Revision Date:	Print Date	Date of last issue: 11.07.2019
1.1	31.10.2019	13.01.2020	Date of first issue: 11.07.2019

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

### Sources of key data used to compile the Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

### Classification of the mixture:

Skin Sens. 1

H317

### Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our up-stream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly. This will be put into practice depending on the register-deadline of the substances involved during the transition period from December 1, 2010 till May 31, 2018.

GB / EN